

MASTERFIBRESA

INNOVATIVE RECYCLED RUBBER SOLUTIONS

MasterPave - Paving the way to a greener future

MasterFibre has just unveiled their new generation **MasterPave** Rubber Pavers. Utilising the latest in manufacturing technology the MasterPave and is now machine made on a vulcanising press. This ensures consistency and world class quality for each and every MasterPave paver that gets manufactured.

The **MasterPave** products are a South African first and are rapidly growing in popularity with property developers and home makers alike. Due to its ease of installation as a DIY product and the ability to manufacture it at varying thicknesses (15mm, 20mm, 25mm, 30mm, 35mm, 40mm, 45mm and 50mm) the **MasterPave** is perfect for everything from Play areas and walkways to entertainment areas and so much more.

MasterPave consists of a versatile material commonly used for commercial, residential, landscaping, sports and fitness purposes. This product has become very popular for several good reasons - they offer an attractive, non-slip, virtually maintenance-free and extremely durable flooring system.

We keep a firm focus on being environmentally responsible and providing ecologically sound solutions. MasterPave Rubber Straight or Interlocking Pavers are made from EPDM (top layer) and recycled tyre rubber (bottom layer).

MasterPave Rubber Pavers have earned their reputation for being extremely tough and long-lasting from their shock-absorbing qualities, which makes these rubber pavers able to handle high-impact and high traffic environments. The **MasterPave** material can be permanently bonded to a variety of surfaces with the use of an adhesive or you could choose the range of Rubber Interlocking Pavers, which require no adhesive and can be removed and replaced with great ease.

MasterFibre SA(Pty) Ltd – Reg. No.: 2017/649409/07 – VAT No. 4610283360
35 Coronation Road, Maitland, 7405
P.O. Box 13051, Woodstock, 7915
Cape Town – Tel (021)511 7411 - Fax (021) 511 7412
Website: www.masterfibre.co.za - E-mail info@masterfibre.co.za

Directors – A. Steyn

Applications:

Due to the product's non-slip properties, **MasterPave** Straight or Interlocking Rubber Pavers are suitable for use on sidewalks, driveways, playgrounds, and even for stable matting. These rubber pavers are great for use in outdoor areas like garden paths, around the swimming pool, on patios, verandas and balcony floors.

Specifications:

- Thickness: 15mm, 20mm, 25mm, 30mm, 35mm, 40mm, 45mm and 50mm
- Size: 220mm x 110mm each
- 41.5 Pavers (220mm x 110mm) = 1 m²
- Average weight 20mm: 17.32 kg/m²
- Straight of Interlocking with beveled edge

Advantages:

- Eco-friendly - consists of recycled material
- Non-slip surface helps ensure safety
- Very low maintenance
- Very easy to install – no power tools required
- Long lifespan
- Will not chip, crack or break
- Weatherproof even in extreme climatic conditions
- Colours can be customised to suited your esthetics

Installation:

MasterPave Interlocking Rubber Pavers are extremely easy to install. Once you've measured the size of the area you want to cover, it is easy to calculate and order the number of pavers required. If necessary, they can easily be cut to size or shape with the use of a utility knife. All that remains is to lay the pavers in your chosen pattern.

A proper foundation is essential for achieving the best results when installing MasterPave Interlocking Rubber Pavers. Depending on where you want to use the pavers, you might need to prepare your foundation. Once you have finished any excavation required, add a layer of crushed stone aggregate as your base material. This will make your foundation permeable, ensuring optimum drainage.

Important factors to keep in mind:

Rubber Pavers must remain dry prior to installation. Rubber pavers are porous and can absorb water which may cause them to expand. Expansion or contraction due to heat is another factor to be avoided prior to installation - just as pavers need to stay dry before installation, they should also be exposed to as little sunlight as possible. The surface of MasterPave Interlocking Rubber Pavers can also absorb dust and paint, and should therefore be covered with a protective material if they could be exposed to any of these elements – particularly in a construction environment.

Guidelines for maintenance:

MasterPave Interlocking Rubber Pavers are virtually maintenance-free, meaning there are no time-consuming or costly maintenance measures to be considered.

A high-pressure water hose is recommended for cleaning the surface of the pavers. Failing this, a simple sweep or mop (with or without water) will also suffice. No detergents are necessary.

In the unlikely event that a paver is damaged, it can be removed replaced at minimal cost and with very little effort.